



Connector LLS170



Application

Corner connector

Suitable for Larssen Z sheet piles

Properties

Steel grade:	S355J2	
Standard lengths:	8 m, 11.8 m	26.25 ft, 38.7 ft (hot rolled)
Steel thickness:	9 mm	0.35"
Weight:	17.63 kg/m	11.85 lbs/ft

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 0.025" per foot (2 mm per meter). Tolerance of steel thickness $\pm 0.04"$ (± 1 mm). Length tolerance up to $\pm 7.9"$ (± 200 mm). Degree details refer to the connector bar axes. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility.

SteelWall ISH GmbH
 Tassilostr. 21
 82166 Gräfelfing
 Germany
 E-mail: info@steelwall.eu

SteelWall US, Humphrey Chang
 US sales line 8:30 am to 4:30 pm (Arizona time)
 Toll free 1(888) 309 2250
 Fax: 1(888) 743 7712
 E-mail: chang@steelwallus.com

Australia
 Caribbean
 New Zealand
 North America
 South East Asia

Copyright by
 SteelWall ISH GmbH
 2023-Nov.-20

steelwallus.com