



## Connector LPB100-9A



### Applications

Pipe pile steel walls, pipe pile combined steel walls

H pile combined steel walls, junctions

### Properties

Steel grade:	S355
Standard lengths:	8 m, 11.8 m 26.25 ft, 38.7 ft, hot rolled
Steel thickness:	9 mm 0.35"
Weight:	9.05 kg/m 6.08 lbs/ft
Max. tensile strength:	912 kN/m 5.2 kips/in

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 0.025" per foot (2 mm per meter). Tolerance of steel thickness  $\pm 0.04"$  ( $\pm 1$  mm). Length tolerance up to  $\pm 7.9"$  ( $\pm 200$  mm). Degree details refer to the connector bar axes. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility. Welding base of LPB and FD connectors can be straight or bevelled.

SteelWall ISH GmbH  
Tassilostr. 21  
82166 Gräfelfing  
Germany  
E-mail: [info@steelwall.eu](mailto:info@steelwall.eu)

SteelWall US, Humphrey Chang  
US sales line 8:30 am to 4:30 pm (Arizona time)  
Toll free 1(888) 309 2250  
Fax: 1(888) 743 7712  
E-mail: [chang@steelwallus.com](mailto:chang@steelwallus.com)

Australia  
Caribbean  
New Zealand  
North America  
South East Asia

Copyright by  
SteelWall ISH GmbH  
2022-May-07

[steelwallus.com](http://steelwallus.com)