



Connector LPB180-16



Applications

Pipe pile steel walls

H pile steel walls

Not suitable for Larssen sheet piles

Properties

Steel grade:	S355	
Standard lengths:	8 m, 11.8 m	26.2 ft, 38.7 ft, hot rolled
Steel thickness:	16 mm	0.63"
Weight:	22.4 kg/m	15.05 lbs/ft

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 0.025" per foot (2 mm per meter). Tolerance of steel thickness $\pm 0.04"$ (± 1 mm). Length tolerance up to $\pm 7.9"$ (± 200 mm). Degree details refer to the connector bar axes. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility. Welding base of LPB and FD connectors can be straight or bevelled.

SteelWall ISH GmbH
Tassilostr. 21
82166 Gräfelfing
Germany
E-mail: info@steelwall.eu

SteelWall US, Humphrey Chang
US sales line 8:30 am to 4:30 pm (Arizona time)
Toll free 1(888) 309 2250
Fax: 1(888) 743 7712
E-mail: chang@steelwallus.com

Australia
Caribbean
New Zealand
North America
South East Asia

Copyright by
SteelWall ISH GmbH
2022-May-10

steelwallus.com