



**Connector LOTn**



**Application**

T connector  
 Suitable for Larssen sheet piles

**Properties**

Steel grade:	S355	
Steel thickness:	8 mm	0.32"
Standard length:	13.8 m	45.2 ft, hot extruded
Weight:	17.2 kg/m	11.56 lbs/ft

Connector is **not suitable for single driving**. Please insert the connector before driving into the sheet pile interlock, tack it with welds and drive it together with the sheet pile (EN12063).

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 0.025" per foot (2 mm per meter). Tolerance of steel thickness  $\pm 0.04"$  ( $\pm 1$  mm). Length tolerance up to  $\pm 7.9"$  ( $\pm 200$  mm). Degree details refer to the connector bar axes. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility.

SteelWall ISH GmbH  
 Tassilostr. 21  
 82166 Gräfelfing  
 Germany  
 E-mail: info@steelwall.eu

SteelWall US, Humphrey Chang  
 US sales line 8:30 am to 4:30 pm (Arizona time)  
 Toll free 1(888) 309 2250  
 Fax: 1(888) 743 7712  
 E-mail: chang@steelwallus.com

Australia  
 Caribbean  
 New Zealand  
 North America  
 South East Asia

Copyright by  
 SteelWall ISH GmbH  
 2022-May-12

[steelwallus.com](http://steelwallus.com)